

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

### Listing of Claims

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. (Previously Presented) A machine-implemented method comprising:

receiving, by a first process in a first user virtual memory address space, a shortcut to a physical address associated with a level of a multi-level virtual address translation table;

posting a descriptor, the descriptor comprising a virtual address in the first user virtual memory address space and the shortcut, to an interface between the first process and a second process, wherein the second process is in a second user virtual memory address space; and

determining, by the second process, the physical address corresponding to the virtual address based on at least the virtual address and the shortcut.

2. (Previously Presented) The method of claim 1 further comprising transferring data to or from a buffer located at the physical address.

3. (Original) The method of claim 1 further comprising: generating the shortcut by a third process.

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

4. (Original) The method of claim 3 wherein generating the shortcut by the third process comprises:

receiving a request to register a virtual buffer, the request including a virtual address corresponding to the start of the virtual buffer;

determining the physical address of one level of the multi-level address translation table associated with the virtual memory space in which the virtual buffer resides; and

generating a shortcut based on the physical address of the one level of the multi-level address translation table.

5. (Original) The method of claim 4 wherein generating a shortcut further comprises:

generating the shortcut based on a key unknown to the first process.

6. (Original) The method of claim 4 wherein generating a shortcut further comprises:

generating the shortcut based on a function unknown to the first process.

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

7. (Original) The method of claim 1 further comprising:  
retrieving a key by the second process; and  
applying the key to the shortcut to produce the physical  
address associated with one level of a multi-level virtual  
address translation table.

8. (Previously Presented) The method of claim 1 further  
comprising determining if the physical address is associated  
with the virtual address.

9. (Original) The method of claim 1 further comprising  
determining if the virtual page containing the virtual address  
is pinned into physical memory.

10. (Original) The method of claim 1 wherein the  
interface is a virtual interface.

11. (Original) The method of claim 1 further comprising  
determining if the first process is authorized to access the  
virtual address.

12. (Original) The method of claim 1 further comprising  
determining if descriptors posted to the interface between the  
first process and second process are authorized to access the  
virtual address.

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

13. (Original) The method of claim 1 further comprising:  
receiving, by a first process, a plurality of shortcuts,  
each shortcut to a physical address associated with a level of a  
multi-level virtual address translation table.

14. (Original) The method of claim 4 wherein generating a  
shortcut comprises:

applying a function,  $F$ , to the physical address of the one  
level and a key.

15. (Original) The method of claim 14 wherein the key is  
associated with the interface between the first and second  
process.

16. (Original) The method of claim 14 wherein the key is  
associated with the first process.

17. (Previously Presented) A machine-implemented method  
comprising:

generating, by a first user process in a first user virtual  
memory address space, a request to register a virtual buffer,  
wherein the virtual buffer is in the first user virtual memory  
address space and is mapped to physical memory by a multi-level  
virtual address translation table associated with the first user  
process;

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

identifying a block of memory that includes the physical address corresponding to the start of the virtual buffer;

generating, by a second process, one or more shortcuts that map the block of memory that includes the physical address corresponding to the start of the virtual buffer; and

transmitting a request to a third user process in a second user virtual memory address space to perform an input or output operation on the virtual buffer.

18. (Previously Presented) The method of claim 17 wherein generating a shortcut further comprises:

generating the one or more shortcuts based on a key that is unknown to the first process.

19. (Previously Presented) The method of claim 17 wherein generating a shortcut further comprises:

generating the shortcut based on a function that is unknown to the first process.

20. (Previously Presented) The method of claim 17 further comprising determining the physical address of the virtual address based on the virtual address and the shortcut, wherein the request includes the shortcut and a virtual address associated with the virtual buffer.

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

21. (Previously Presented) The method of claim 20 further comprising:

determining if the physical address is associated with the virtual address; and

if the physical address is associated with the virtual address, then enabling the input or output operation on at least part of the virtual buffer.

22. (Previously Presented) The method of claim 20 further comprising:

determining if physical pages associated with the physical address are pinned into physical memory; and

if the associated virtual pages are pinned into physical memory, then enabling the input or output operation.

23. (Previously Presented) The method of claim 20 further comprising:

determining if the third user process is authorized to access the associated virtual buffer; and

if the third user process is authorized to access the associated virtual buffer, then enabling the input or output operation on at least part of the virtual buffer.

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

24. (Previously Presented) The method of claim 20 further comprising:

determining if requests posted to the interface between the first user process and the third user process are authorized to access the associated virtual buffer; and

if requests to the interface are authorized to access the associated virtual buffer, then enabling the input or output operation on at least part of the virtual buffer.

25. (Previously Presented) The method of claim 18 further comprising:

transmitting a request to a third user process in a second virtual memory address space to perform an input or output operation on the virtual buffer, wherein the request includes one of the one or more shortcuts and a virtual address associated with the virtual buffer; and

determining a physical address of the virtual address based on the virtual address, the shortcut, and the key.

26. (Currently Amended) A system comprising:

a first processor ~~capable of~~ configured to:

~~executing~~ execute instructions of a first process which causes the first processor to produce a shortcut to a physical address associated with a level of a multi-level virtual address translation table, and

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

~~executing~~ execute instructions of a second user process in a first user virtual memory address space which causes the first processor to post a descriptor comprising a virtual address and the shortcut to an interface; and  
a second processor ~~capable of~~ configured to ~~executing~~ execute instructions of a third user process in a second user virtual memory address space which cause the second processor to:

read the descriptor posted on the interface, and  
determine a physical address of the virtual address based on at least the virtual address and the shortcut,  
wherein the interface is between the second process and the third process.

27. (Original) The system of claim 26 wherein the instructions of the first process cause the first processor to encrypt the shortcut with a key.

28. (Previously Presented) The system of claim 27 wherein the instructions of the third user process cause the second processor to:

retrieve the key; and  
apply the key to the shortcut to produce the physical address associated with one level of a multi-level virtual address translation table.



Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

29. (Previously Presented) The system of claim 28 wherein the instructions of the third user process cause the second processor to determine if the physical address is associated with the second user process.

30. (Previously Presented) The system of claim 28 wherein the instructions of the third user process cause the second processor to determine if physical pages associated with the physical address are pinned into physical memory.

31. (Previously Presented) The system of claim 28 wherein the instructions of the third user process cause the second processor to determine if the second user process is authorized to access the virtual buffer.

32. (Previously Presented) The system of claim 27 wherein the instructions of the third user process cause the second processor to determine if requests posted to the interface between the second user process and the third user process are authorized to access the virtual buffer.

33. (Previously Presented) A computer program product residing on a computer readable medium having instructions stored thereon that, when executed by the processor, cause that processor to:

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

produce a shortcut to a physical address associated with a level of a multi-level virtual address translation table; and write a descriptor comprising a virtual address and the shortcut to an interface between a first user process in a first user virtual memory address space and a second user process in a second user virtual memory address space.

34. (Original) The product of claim 33 having instructions that further cause the processor to encrypt the shortcut with a key.

35. (Original) The product of claim 33 having instructions that further cause the processor to encrypt the shortcut with a function.

36. (Previously Presented) A computer program product residing on a computer readable medium having instructions stored thereon that, when executed by a processor performing operations in a first user virtual memory address space, cause that processor to:

read a message posted on an interface by a first user process in a different user virtual memory address space, the message including a shortcut to a physical address associated with a level of a multi-level virtual address translation table;

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

determine a physical address of a virtual address in the different user virtual memory address space based on at least the virtual address and the shortcut; and

transmit a message over a network based on contents of the physical address.

37. (Original) The product of claim 36 having instructions that further cause the processor to:

retrieve a key; and

apply the key to the shortcut to produce the physical address associated with one level of a multi-level virtual address translation table.

38. (Previously Presented) The product of claim 36 having instructions that further cause the processor to determine if the physical address is associated with the virtual address.

39. (Previously Presented) The product of claim 36 having instructions that further cause the processor to determine if virtual pages referenced by the message are pinned in physical memory.

40. (Previously Presented) The product of claim 36 having instructions that further cause the processor to determine if the first process is authorized to access a virtual buffer referenced by the message.

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

41. (Previously Presented) The product of claim 36 having instructions that further cause the processor to determine if messages posted on the interface are authorized to access the virtual buffer.

42. (Currently Amended) A system comprising:  
a client computer; and  
a server in communication with the client computer using a network, the server comprising:  
a first processor ~~capable of~~ configured to producing  
produce a shortcut to a physical address associated with a level of a multi-level virtual address translation table and ~~writing~~  
write a descriptor comprising a virtual address in a first user virtual memory address space and the shortcut to an interface;  
and  
a second processor ~~capable of~~ configured to performing  
perform operations in a second user virtual memory address space, the operations including reading the descriptor posted on the interface, determining a physical address of the virtual address based on at least the virtual address and the shortcut, and transferring data located at the physical address to the client computer using the network.

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

43. (Currently Amended) The system of claim 42 wherein the first processor is ~~capable of~~ configured to encrypting encrypt the shortcut with a key.

44. (Currently Amended) The system of claim 43 wherein second processor is ~~capable of~~ configured to decrypting decrypt the shortcut to produce the physical address associated with one level of a multi-level virtual address translation table.

45. (Original) The system of claim 42 wherein the interface is a virtual interface.

46. (Currently Amended) A system comprising:  
a storage device; and  
a server in communication with the storage device over a network, the server comprising:  
a first processor ~~capable of~~ configured to producing produce a shortcut to a physical address associated with a level of a multi-level virtual address translation table and ~~writing~~ write a descriptor comprising a virtual address in a first user virtual memory address space and the shortcut to an interface, and

a second processor ~~capable of~~ configured to performing perform operations in a second user virtual memory address space, the operations including reading the descriptor posted on the interface, determining a physical address of the virtual

Attorney's Docket No.: 10559-900001 /P17948  
Intel Corporation

address based on at least the virtual address and the shortcut,  
and transferring data located at the physical address to the  
storage device using the network.

47. (Currently Amended) The system of claim 46 wherein  
the first processor is ~~capable of~~ configured to encrypting  
encrypt the shortcut with a key.

48. (Currently Amended) The system of claim 47 wherein  
second processor is ~~capable of~~ configured to decrypting decrypt  
the shortcut to produce the physical address associated with one  
level of a multi-level virtual address translation table.

49. (Original) The system of claim 46 wherein the  
interface is a virtual interface.